

SPECIFICATIONS

SS-SPD-U*


Surge Protection Device

Model: SS-SPD-US10P4、SS-SPD-US10P5、
SS-SPD-UP10P

Description: Surge Protection Device

Rev.: V00

Release Date: 2025-12-04



SS-SPD-U*

Features

- Wiring method: Single-live wire series connection: SS-SPD-US10P4
Series Connection: SS-SPD-US10P5
Parallel connection: SS-SPD-UP10P
- Operating voltage: 90-305Vac
- Excellent surge resistance with low residual voltage
- Test category: EN 61643-11 – T2 & T3、IEC 61643-11 - Test Class II & Class III
- Waterproofing IP rating: IP67
- Reference standard: IEC61643-11, EN61643-11
- Surge protection: L-N、L-PE、N-PE

TDK MOV+GDT inside



IP67 RoHS

Description

The SS-SPD-U* is a specially designed surge protection device, specifically used to provide a higher level of surge protection and transient overvoltage protection for LED drivers in applications such as street lighting, industrial lighting, sports lighting, and commercial lighting. The product is characterized by high quality, high stability, convenient installation, good safety, long service life, and low maintenance costs. It can deliver a higher level of surge protection for LED drivers, ensuring stable operation without damage, thereby effectively preventing equipment failure.


Applications: street lights, tunnel lights,sports, industrial and commercial lighting systems.

Technical Parameters

Parameters	Numerical value
Rated Input Voltage Range	100-277Vac
Maximum Input Voltage Range	90-305Vac
Maximum continuousoperating voltage	320Vac
Input frequency	47-63Hz Typ:50/60Hz
Open circuit voltage Uoc	10kV @ 1.2/50us
Voltage Protection Level Up	<1500V Typ:1300V L-N
Voltage Protection Level Up	<2000V Typ:1800V L/N-PE
Nominal discharge current In	≤ 5kA @ 8/20μs electric current wave
Maximum discharge current Imax	≤10kA @ 8/20μs electric current wave
Rated load current IL	≤ 7A Series-type
Operating Ta	-40~+85°C
Storage Ta	-40~+85°C
End-of-life indication	Light ON: SPD is functional Light OFF: SPD has reached end-of-life
Weight	45g

Test Waveform:



Number of lightning strikes



Short circuit current waveform


Lightning Surge Test 8/20μs	
Surge magnitude	Number of impacts
10000A	2
7000A	4
5000A	30

Voltage Protection Level Up




Ic 8/20μs	Differential mode U2	Common mode U2/U1
1kA	≤1100V	≤1100/1800V
3kA	≤1300V	≤1300/1800V
5kA	≤1500V	≤1500/2000V

SS-SPD-USxxx4 Series: Enclosure Dimensions:



Wiring Method:




Notes:

1. Brown: Li, Black: Lo, Blue: Ni, Yellow-Green: PE;
2. Wire gauge: UL 1015, 18AWG ,105°C, 600V, Exposed Length 150±10mm, Tinned length of wire:10±2mm
3. Shell color: Black
4. Shell material: PC(UL94-V0).


SS-SPD-USxxx5 Series:

Enclosure Dimensions:



Unit: mm

Wiring Method:




Notes:


1. Brown: Li, Black: Lo, Blue: Ni, White: No, Yellow-Green: PE;
2. Wire gauge: UL 1015, 18AWG, 105°C, 600V, Exposed Length 150±10mm, Tinned length of wire: 10±2mm
3. Shell color: Black
4. Shell material: PC(UL94-V0).

SS-SPD-UPxxx Series:

Enclosure Dimensions:



Wiring Method:



Notes:

1. Brown: Li, Blue: Ni, Yellow-green: PE;
2. Wire gauge: UL 1015, 18AWG ,105°C,600V ,Exposed Length 150±10mm ,Tinned length of wire:10±2mm
3. Shell color: Black
4. Shell material: PC(UL94-V0).

Package

- Outside carton dimension: L×W×H =495mm×385mm×162mm;
- 112PCS/Carton;
- Net weight/Piece0.045kg;Gross weight/Carton: 6.25kg;

Transportation

Packaging is designed suitable for transportation by trucks, vessels and flights. The products should be avoided direct sunlight and rain, loaded/unloaded with caution.

Storage

The product storage meets the standard of the GB 3873—83.
Products should be rechecked if stored for over 1 year before assembly.

RoHS

Products comply with RoHS Directive (2011/65/EU) and amendment 2015/863/EU.

Revision History

Version	Description of Update	Updated Date	Remark
V00	Original Release	2025/12/04	